

Redmine - Defect #13165

rdm-mailhandler.rb: initialize_http_header override basic auth

2013-02-13 23:18 - Jean-Louis Fuchs

Status:	Closed	Start date:	
Priority:	Normal	Due date:	
Assignee:	Jean-Philippe Lang	% Done:	0%
Category:	Email receiving	Estimated time:	0.00 hour
Target version:	2.2.4	Affected version:	2.2.3
Resolution:	Fixed		
Description			
<p>request.initialize_http_header() and request.basic_auth should be switched. One has to initialize the headers first and then set basic auth, since basic auth will change the headers.</p> <p>As the problem still exists in trunk is suppose this affects all versions of redmine. Patch attached.</p>			

Associated revisions

Revision 11371 - 2013-02-14 18:52 - Jean-Philippe Lang

Fixed that initialize_http_header overrides basic auth in rdm-mailhandler.rb (#13165).

Patch by Jean-Louis Fuchs.

Revision 11593 - 2013-03-11 19:22 - Jean-Philippe Lang

Merged r11371 from trunk (#13165).

History

#1 - 2013-02-14 18:53 - Jean-Philippe Lang

- Status changed from New to Resolved
- Assignee set to Jean-Philippe Lang
- Target version set to 2.2.4
- Affected version (unused) changed from devel to 2.2.3
- Resolution set to Fixed
- Affected version set to 2.2.3

Fix committed in r11371, thanks for pointing this out.

#2 - 2013-03-11 19:22 - Jean-Philippe Lang

- Status changed from Resolved to Closed

Files

rdm-mailhanlder.rb.patch	588 Bytes	2013-02-13	Jean-Louis Fuchs
--------------------------	-----------	------------	------------------