

Redmine - Feature #30230

Redmine reference with version info

2018-12-16 02:10 - Sho HASHIMOTO

Status:	New	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Documentation	Estimated time:	0.00 hour
Target version:			
Resolution:			

Description

I was generated Redmine reference with version infomation. See below.

- <http://sho-h.github.io/redmine/3.3/index.html>
- <http://sho-h.github.io/redmine/3.4/index.html>
- <http://sho-h.github.io/redmine/4.0/index.html>

This was generated by only executing `bundle exec rake yard`. We can see codes [here](#).

1. Add new [yard template](#)
2. Add [redmine version info](#)
 1. git checkout <ver>
 2. yard doc --no-output && mv .yardoc .yardoc.<ver> # generate only .yardoc
 3. Repeat 1. and 2. with all tag
 4. yard diff .yardoc.<ver1> .yardoc.<ver2>
 5. Repeat 4. with all tag
 6. Reform all 4. and 5. result to redmine_changes.yml
3. Fix yard [rake task](#) to use a new template

I want to publish either of the following to maintenance redmine plugins easily.

- redmine.github.io/redmine/<ver>/ # need to create gh-pages branch on Github mirror
- yardoc.redmine.jp/Redmine/<ver>/ # need to talk with @g_maeda san?

History

#1 - 2018-12-16 03:02 - Sho HASHIMOTO



[#28996](#) is related with this ticket.

#2 - 2018-12-16 03:10 - Sho HASHIMOTO

We can see codes here.

Maybe, version info should be belongs to generator only to generate past version.
I will create redmine plugin to overwrite rake yard task(in lib/tasks/yardoc.rake) and maintain it if this suggestion will be accept.

Files

 2018-12-16 9.34.39.png	51 KB	2018-12-16	Sho HASHIMOTO
 2018-12-16 9.39.25.png	98.1 KB	2018-12-16	Sho HASHIMOTO