

## Redmine - Feature #3057

### Allow custom my\_page blocks to define drop-down names

2009-03-26 23:07 - Brad Beattie

<b>Status:</b>	Closed	<b>Start date:</b>	2009-03-26
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>		<b>% Done:</b>	0%
<b>Category:</b>	Plugin API	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	0.9.0		
<b>Resolution:</b>	Fixed		

**Description**

I have [a plugin that adds additional blocks to the my\\_page page](#). The only problem I have here is that I can't name the blocks beyond their file names, whereas core blocks define their localized names:

```
BLOCKS = { 'issuesassignedtome' => :label_assigned_to_me_issues,  
          'issuesreportedbyme' => :label_reported_issues,  
          'issueswatched' => :label_watched_issues,  
          'news' => :label_news_latest,  
          'calendar' => :label_calendar,  
          'documents' => :label_document_plural,  
          'timelog' => :label_spent_time  
        }.merge(Redmine::Views::MyPage::Block.additional_blocks).freeze
```

This request is necessary in order to localize the plugin.

#### Associated revisions

##### Revision 2659 - 2009-04-05 15:33 - Jean-Philippe Lang

Set a default scope for 'My page' block names translations (#3057).

#### History

##### #1 - 2009-03-30 22:21 - Jean-Philippe Lang

Actually, you can add a key in your locales that matches the partial name, eg:

```
_my_partial.rhtml => uses 'my_partial' translation key if available
```

Maybe we could use a prefix for these translations in locales, eg: 'my.blocks.my\_partial' or something. What do you think?

##### #2 - 2009-03-30 22:33 - Brad Beattie

Jean-Philippe Lang wrote:

Actually, you can add a key in your locales that matches the partial name, eg:

```
_my_partial.rhtml => uses 'my_partial' translation key if available
```

Maybe we could use a prefix for these translations in locales, eg: 'my.blocks.my\_partial' or something. What do you think?

Hrm. A prefix would be nice as it would help avoid any unintended overlap. Not necessary, but nice.

##### #3 - 2009-04-05 15:30 - Jean-Philippe Lang

- Status changed from New to Resolved

- Target version set to 0.9.0

- Resolution set to Fixed

Committed in [r2659](#).

Default scope is 'my.blocks', so you can have:

```
my:  
  blocks:  
    block_name: Localized block name
```

or (if not found):

```
block_name: Localized block name
```

**#4 - 2009-11-15 14:23 - Jean-Philippe Lang**

- *Status changed from Resolved to Closed*

**#5 - 2011-10-25 13:00 - Jedidiah Lira**

- *Assignee deleted (Eric Davis)*

SPAM