

Redmine - Feature #32090

REST API: users: add support for status=*

2019-09-18 18:34 - Martin von Wittich

| | | | |
|--|-----------|-----------------|-----------|
| Status: | Closed | Start date: | |
| Priority: | Normal | Due date: | |
| Assignee: | | % Done: | 0% |
| Category: | REST API | Estimated time: | 0.00 hour |
| Target version: | | | |
| Resolution: | Duplicate | | |
| Description Currently, the /users.:format REST API will default to status=1 (active), that is, when you attempt to search for a certain user (redmine-admin.auth contains an API token of an administrator in the format -u TOKEN:x): <pre>curl -H 'Content-Type: application/json' \ -G -K redmine-admin.auth \ 'https://redmine.example.com/users.json?name=firstname.lastname'</pre> it will only return the requested account when the account is active. This means that I have to make two request for status=1 and status=3 to find a user when I don't know if the account is locked or not :(I would have suspected that status=* would return all kinds of users, similarly to how it works for Rest Issues with status_id=*, but this is apparently not the case. | | | |
| Related issues: Is duplicate of Redmine - Defect #40099: User api filtering by status=* broke... Closed | | | |

History

#1 - 2019-09-19 03:46 - Go MAEDA

You can get users with any status by adding 'status=' parameter.

```
curl --user admin:password 'http://redmine.example.com/users.json?status='
```

#2 - 2019-09-19 14:11 - Martin von Wittich

- Status changed from New to Resolved

Go MAEDA wrote:

You can get users with any status by adding 'status=' parameter.

That does exactly what I wanted, thanks! I've updated the wiki accordingly.

#3 - 2019-09-19 17:38 - Martin von Wittich

Hm, there is one other issue I've stumbled over - users.json?name=foobar&status= won't return the status of the matched users. I either have to query the statuses separately (users.json?name=foobar&status=1 and so on) so I know that all matched users have the status I just queried, or I have to query each returned user separately with users/<id>.json to get the user's status. Is that intentional, or could a status field be added to users.:format?

#4 - 2021-02-20 17:44 - Yar n

This is so extremly not obvious.
Is it possible to update documentation to point to that feature?

#5 - 2024-01-25 16:39 - Marius BĂLTEANU

- Is duplicate of Defect #40099: User api filtering by status=* broke on upgrade from 5.0 to 5.1 added

#6 - 2024-01-25 16:43 - Marius BĂLTEANU

- Status changed from Resolved to Closed
- Resolution set to Duplicate

The behaviour changed as follow:

- Redmine <= 5.0.*: you can use status= to get all users from API
- Redmine 5.1.0 and 5.1.1: you can only use users.json?f[]=status_id&op[status_id]==&v[status_id][]=1&v[status_id][]=2&v[status_id][]=3 to get all users because of [#40099](#).
- Redmine >= 5.1.2: you can use status= which is now deprecated in favour of status=* or the long syntax
- Redmine 6.0: you can only use status=* or the long syntax