

Redmine - Patch #6475

Add an option to set the project name from apache when authenticating with Redmine.pm

2010-09-23 14:08 - Sergio Talens-Oliag

Status:	New	Start date:	2010-09-23
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	SCM extra	Estimated time:	0.00 hour
Target version:			
<p>Description</p> <p>I have some repositories that are configured with SVNPath instead of SVNParentPath (I'm doing it to be able to use additional authentication methods them, see issue #6414).</p> <p>With the current Redmine.pm code (1.0.1) the authentication against Redmine fails because the project_id is not guessed as it should (the apache Location points to the repository, not to it's parent path).</p> <p>To solve the problem I've patched Redmine.pm to allow the use of a new option that adjusts the project_id to use; if the option is set the get_project_identifier function returns that name instead of calculating it from the URI and the apache location).</p> <p>The attached patch is against an export of the redmine-1.0.1 tag.</p>			

History

#1 - 2010-09-23 14:10 - Sergio Talens-Oliag

- File Redmine.pm-Get_project_id_from_apache.diff added

#2 - 2011-03-29 07:14 - Toshi MARUYAMA

- Category changed from SCM to SCM extra

Files

Redmine.pm-Get_project_id_from_apache.diff	1 KB	2010-09-23	Sergio Talens-Oliag
Redmine.pm-Get_project_id_from_apache.diff	2.12 KB	2010-09-23	Sergio Talens-Oliag