Redmine - Feature #7346

Allow a default version to be set on the command line for incoming emails

2011-01-17 08:06 - Garry Fallon

Status:	Closed	**Start date:**	2011-01-17
Priority:	Normal	**Due date:**	
Assignee:	Jean-Philippe Lang	**% Done:**	0%
Category:	Email receiving	**Estimated time:**	0.00 hour
Target version:	3.2.0		
Resolution:	Fixed		

Description

Feature #5622 added support to allow the target_version (*fixed_version* in the implementation) to be set in the contents on an incoming email; this is a useful addition.

It would be really useful to also allow a default version to be set on the command line (for new tickets) when calling receive_pop3 or receive_imap. This would be really useful in cases where you want all new tickets to be added to a version such as 'Unassigned Backlog", "For Review", etc...

This is a very minor change to redmine/lib/tasks/email.rake to add fixed_version to the list of attributes that can be set for both :receive_pop3 and :receive_imap, and add a relevant description to the command line help. e.g. replace %w(project status tracker category priority).each { |a| options[:issue][a.to_sym] = ENV[a] if ENV[a] }
with %w(project status tracker category priority fixed_version).each { |a| options[:issue][a.to_sym] = ENV[a] if ENV[a] }

Associated revisions

Revision 14789 - 2015-11-01 09:56 - Jean-Philippe Lang

Allow a default version to be set on the command line for incoming emails (#7346).

History

#1 - 2015-11-01 09:56 - Jean-Philippe Lang

- Status changed from New to Closed

- Assignee set to Jean-Philippe Lang

- Target version set to 3.2.0

- Resolution set to Fixed

Feature added in r14789.