

Redmine - Defect #8978

LDAP timeout if an LDAP auth provider is unreachable

2011-08-03 16:21 - Davide Ferrari

Status:	Closed	Start date:	2011-08-03
Priority:	Normal	Due date:	
Assignee:	Jean-Philippe Lang	% Done:	0%
Category:	LDAP	Estimated time:	0.00 hour
Target version:	2.1.0	Affected version:	
Resolution:	Fixed		
Description			
Hi			
we are using Redmine with a like 3 different LDAP auth sources, and sometimes if one of the goes down, almsot every process involved with Redmine slow down terribly.			
It seems that when some use rtry to log in, Redmien try to contact the server that's not responding, waiting indefinitely for the action to be completed, making everything slow. There should be a (configurable perhaps?) timeout (I think that a sane default could be 30 seconds), and then the LDAP source should be considered dead (at least for that request).			
i'm using Redmine 1.1.2.stable.5317			

Associated revisions

Revision 9931 - 2012-07-07 11:36 - Jean-Philippe Lang

Adds a configurable timeout for LDAP authentication (#8978).

Revision 9932 - 2012-07-07 11:37 - Jean-Philippe Lang

Fills locales (#8978).

History

#1 - 2011-08-04 00:04 - Terence Mill

you can try if [redmine_ldap_sync](#) can handle this better.

#2 - 2012-06-29 03:21 - Brett Patterson

I can confirm this happens in 2.0.3 as well. We used to use LDAP to authenticate and when we took our LDAP system offline I forgot some users were still configured and instead of seeing a message about unable to log in or LDAP authentication server unreachable, it gave a 500 error.

#3 - 2012-06-29 04:32 - Brett Patterson

- *File ldap_timeout-v2.0.3.patch added*

Here's a quick patch I made against 2.0.3. This will catch a timeout error after 30 seconds and redirect the user with a proper error message. This is english only and really is a proof-of-concept. Ideally the timeout would default to 30 seconds but could be modified via the administration settings (or per-LDAP definition).

Perhaps the Timeout class is not the best solution in this case; however, from my testing it works.

#4 - 2012-06-29 10:36 - Etienne Massip

- *Target version set to Candidate for next major release*

Brett Patterson wrote:

Perhaps the Timeout class is not the best solution in this case; however, from my testing it works.

Actually seems to be a great idea.

#5 - 2012-06-30 04:10 - Brett Patterson

- *File ldap_timeout_v2-redmine2.0.3.patch added*

Worked on it some more and now the timeout is configurable on a per-connection basis in the LDAP settings. If no timeout value is set, the default of 20 is set.

In order to use this, the following SQL must be run:

```
ALTER TABLE `auth_sources` ADD COLUMN `timeout` int(11) DEFAULT NULL AFTER `port`;
```

#6 - 2012-07-06 21:35 - Jean-Philippe Lang

- Target version changed from Candidate for next major release to 2.1.0

Is there a good reason to set the timeout for each LDAP instead of a global setting?

#7 - 2012-07-06 23:34 - Brett Patterson

A good reason not really. It may be preferable to have "local" LDAP connections have a faster timeout than remote ones, so there may be some instances where adding an extra second here and there is preferable.

#8 - 2012-07-07 11:36 - Jean-Philippe Lang

- Status changed from New to Closed

- Assignee set to Jean-Philippe Lang

- Resolution set to Fixed

Feature added in [r9931](#) with slight changes and test. Thanks.

#9 - 2012-07-07 11:56 - Davide Ferrari

Thanks a lot!

Files

ldap_timeout-v2.0.3.patch	2.46 KB	2012-06-29	Brett Patterson
ldap_timeout_v2-redmine2.0.3.patch	3.91 KB	2012-06-30	Brett Patterson