

Redmine - Patch #986

Clone remote git repository

2008-04-03 19:27 - Michael Bumann

Status: Closed	Start date: 2008-04-03
Priority: Normal	Due date:
Assignee:	% Done: 0%
Category: SCM	Estimated time: 0.00 hour
Target version:	

Description

this patch clones the repository of a remote GIT repository.
enter the public clone URL (git://.../.git) it will clone it to RAILS_ROOT/repositories/git/<project identifier>/<repository name>
It also changes the URL to use the local clone.

Related issues:

Related to Redmine - Feature #2580: Remote git repositories	Closed	2009-01-25	
Related to Redmine - Feature #6515: Mercurial hgrc support with issues auto-s...	New	2010-09-28	
Related to Redmine - Patch #1783: automatic repository creation	New	2008-08-13	
Related to Redmine - Patch #7494: Patch for support http protocol wirh mercur...	Closed	2011-01-30	2011-01-30

History

#1 - 2008-04-07 20:10 - Jean-Philippe Lang

- Target version deleted (0.7)

#2 - 2008-07-05 15:42 - Thomas Lecavelier

Test cases are missing. I know it wouldn't be easy but you can try to accept "not so remote" repository in tmp dir.

Not tested, but the dir variable in the diff could break if white spaces appear: please protect this var expansion in the command line with simple quotes.

#3 - 2011-12-16 13:28 - Toshi MARUYAMA

- Status changed from New to Closed

As I described [#7494](#) note 2,
I think Redmine core should not have this feature.
It is impossible to test.
Plugins should provide this feature.

#4 - 2012-04-05 11:31 - Gabriel Mazetto

Toshi MARUYAMA wrote:

As I described [#7494](#) note 2,
I think Redmine core should not have this feature.
It is impossible to test.
Plugins should provide this feature.

It is not impossible, it can be a little tricky, but still really possible. A easy test case could be: get a dummy git bare repository in the test folder, then run git-daemon configured to provide this dummy repository. The unit test will have to add a repository from git://localhost/1.git (for example) and then check to see if the folder was correctly created and if it's a git repository.

Also there is the "git" rubygem that can make it easy to clone and fetch revisions:

```
require 'git'  
Git.clone('git://github.com/.../repo.git', '/destination/path.git', :bare => true)
```

and

```
git = Git.open('/destination/path.git', :log => Logger.new(STDOUT))  
git.fetch('origin')
```

It can't be easier then that. Implementing this "feature" will make redmine usable with git.

Files

clone_remote_git.diff

1.68 KB

2008-04-03

Michael Bumann